


Description

Lapox ARD-14 is a low viscosity, aliphatic monoepoxide reactive diluent, based on n-butyl alcohol. It is compatible with all types of epoxy resin in any proportion. Resins diluted with it can be suitably cured by epoxy curing agents for a variety of applications. Higher proportion imparts flexibility in the cured system and hence affects glass transition temperature significantly.

Chemical structure



Advantages

- Faster gel time
- Improves wetting and processability
- Provides high filler loading
- Provides very good flexibility
- Reduces viscosity significantly compared to other mono epoxide diluent

Applications

- Adhesives
- Civil engineering and flooring
- Electronic encapsulation
- Laminating
- Potting and tooling

Typical specifications

Properties	Unit	Test method	Values
Appearance	-	Visual	Clear liquid
Colour	GS	ASTM D1544	Max 1
Epoxy value	Eq/kg	ASTM D1652	6.2 - 7.3
Epoxy equivalent weight (EEW)	g/eq	ASTM D1652	137 - 161
Viscosity at 25°C	m Pas	ASTM D2196	Max 2
Hydrolysable chlorine	%	ASTM D1726	Max 0.1

Packaging

Lapox ARD-14 is available in 195 kg MS | HDPE drums. Other packing may be considered on request.

Storage and handling

Lapox ARD-14 should be stored in a cool and dry place, preferably in a sealed container and should not be exposed to direct sunlight. This product has a shelf life of 2 years if stored in its original container between 2°C and 40°C away from humidity and excessive heat.

Safety

Wear personal protective equipment (PPE). Avoid contact with the eyes and skin. In case of direct contact and irritation, the resin should be washed off immediately with soap and warm water. Avoid breathing vapours, mist or gas. Please refer to the Safety Data Sheet (SDS) of Lapox ARD-14 for detailed safety instructions.

LAPOX[®] ARD-14

Technical Data Sheet | Polymers Business



Spills and disposal

In case of spills, sweep up and shovel the spilled material. Keep spilled material in suitable, closed containers for disposal. Soak up with an absorbent such as clay, sand or other suitable material. Flush area with water to remove trace residue. Do not allow the product to reach the sewage system. Waste must be disposed of in accordance with federal, state or local regulations, as applicable.

Contact

E-mail: polymers@atul.co.in
Website: www.atul.co.in

Note

Lapox[®] is a registered trademark of Atul Ltd.

Manufacturing site

Atul 396 020, Gujarat, India
Telephone: (+91 2632) 230000 | 233261
E-mail: contact@atul.co.in

Disclaimer: The information contained herein is for information purposes only. While enough care is taken in disclosing the information, users of this information are advised to cross-check the same depending upon use | application. Atul Ltd does not give any assurance or warranty or guarantee in regard to the accuracy or completeness of the information and no claim or liability will be accepted or entertained in regard thereto. Atul Ltd makes no warranty of any kind, expressed or implied, including, but not limited to, any implied warranty of merchantability or fitness for a particular purpose or performance or usage of trade.