

# LAPOX<sup>®</sup> ASH-11 MIC


## (3,3'-Diamino diphenyl sulfone Micronised)

Technical Data Sheet | Polymers Business

### Description

3,3'-DDS (Micronised) is an off-white to yellowish-brown, odourless, non-volatile micronised powder suitable to disperse uniformly in epoxy resins. This is used as curing agent with epoxy resins specially to obtain faster reactivity than 4,4'-DDS, this also offers unique combination of mechanical, electrical, and thermal properties along with higher stiffness in appropriately cured components.

### Chemical structure



### Applications

Electrical moulding compounds (EMC)  
FRP composites  
High performance epoxy coatings  
Manufacturing of polyamides and polyimides  
Prepregs  
Printed circuit boards (PCB)  
Structural adhesives

### Advantages

Excellent high temperature properties  
Excellent thermal stability  
Outstanding mechanical and electrical properties  
Slow reactivity and longer shelf life of prepreg

### Typical specifications

Properties	Unit	Test method	Values
Appearance	-	Visual	off-white to yellowish-brown powder
Assay	%	Titration	Min 99
Melting point	°C	Atul	167 - 175
Water content (by KF)	%	Atul	Max 0.15
Volatile content (105°C / 2 hours)	%	Atul	Max 0.15
Ash content	%	Atul	Max 0.1
Purity	%	HPLC	Min 99
Median particle size D (μ, 0.5)	Micron	Atul	Max 10

### Packaging

3,3'-DDS (Micronised) is available in 25 kg fiber drums. Other packing may be considered on request.

# LAPOX<sup>®</sup> ASH-11 MIC

## (3,3'-Diamino diphenyl sulfone Micronised)

Technical Data Sheet | Polymers Business

**Storage and handling** 3,3'-DDS (Micronised) must be stored below 40°C in a sealed container in dry and well-ventilated place. The shelf life of this product is 3 years if stored at recommended temperature in its original container away from sparks, flame, humidity and excessive heat. Avoid storage near ignition sources, hot environment, and in sunlight.

**Safety** Wear personal protective equipment (PPE). Avoid contact with the eyes and skin. In case of direct contact and irritation, the material should be washed off immediately with soap and warm water. Avoid breathing vapours, mist or gas. Please refer to the Safety Data Sheet (SDS) of 3,3'-DDS (Micronised) for detailed safety instructions.

**Spills and disposal** In case of spills, sweep up and shovel the spilled material. Keep spilled material in suitable, closed containers for disposal. Flush area with water to remove trace residue. Do not allow the product to reach the sewage system. Waste must be disposed of in accordance with federal, state or local regulations as applicable.

**Contact** E-mail: [polymers@atul.co.in](mailto:polymers@atul.co.in)  
Website: [www.atul.co.in](http://www.atul.co.in)

**Note** Lapox<sup>®</sup> is a registered trademark of Atul Ltd.

### Manufacturing site

Atul 396 020, Gujarat, India  
Telephone: (+91 2632) 230000 | 233261  
E-mail: [contact@atul.co.in](mailto:contact@atul.co.in)

Disclaimer: The information contained herein is for information purposes only. While enough care is taken in disclosing the information, users of this information are advised to cross-check the same depending upon use | application. Atul Ltd does not give any assurance or warranty or guarantee in regard to the accuracy or completeness of the information and no claim or liability will be accepted or entertained in regard thereto. Atul Ltd makes no warranty of any kind, expressed or implied, including, but not limited to, any implied warranty of merchantability or fitness for a particular purpose or performance or usage of trade.